



INFRASTRUCTURE REPORT

Interface Utilization

Real-Time Bandwidth & Interface Performance Analysis

REPORT SCOPE

All Monitored Interfaces

GENERATED

July 21, 2026 at 13:47:23

REFERENCE ID

RPT-2026-0721-EE6312

CONFIDENTIAL — INTERNAL USE ONLY

EXECUTIVE SUMMARY

132

TOTAL INTERFACES

0

HIGH UTILIZATION (>80%)

0.0%

AVG UTILIZATION

75.83 GB

INTERFACE THROUGHPUT

INTERFACE DETAILS

DEVICE	INTERFACE	SPEED	STATUS	TOTAL TRAFFIC	IN BPS	OUT BPS	UTILIZATION
NTA-R1	Loopback2113	8 Gbps	UP	0 B	0 bps	0 bps	0.0%
NTA-R1	GigabitEthernet3	1 Gbps	UP	0 B	0 bps	0 bps	0.0%
FG-NETS	mgmt	0 bps	DOWN	0 B	0 bps	0 bps	0.0%
NTA-R3	GigabitEthernet4 (LAN_INTERFACE)	1 Gbps	UP	277.59 KB	0 bps	95 bps	0.0%
NTA-R1	Loopback35 (syslogg_test2)	8 Gbps	UP	0 B	0 bps	0 bps	0.0%
NTA-R3	VoIP-Null0	10 Gbps	UP	0 B	0 bps	0 bps	0.0%
FG-NETS	wan1 (WAN)	1 Gbps	UP	0 B	0 bps	0 bps	0.0%
FG-NETS	wan2	0 bps	DOWN	0 B	0 bps	0 bps	0.0%
NTA-R3	Null0	10 Gbps	UP	0 B	0 bps	0 bps	0.0%
NTA-R1	Loopback36 (usama test)	8 Gbps	UP	0 B	0 bps	0 bps	0.0%
FG-NETS	ha1	0 bps	DOWN	0 B	0 bps	0 bps	0.0%
FG-NETS	ha2	0 bps	DOWN	0 B	0 bps	0 bps	0.0%

